

VADO SL EQ STEP-THROUGH



DAS VADO SL ST IST DIE ERSTE WAHL FÜR SPORTLICHE CITY-RIDER, DIE WERT AUF SUPER GERINGES GEWICHT LEGEN

FEDERLEICHT: LEICHTER ALS VERGLEICHBARE E-BIKES DANK SPECIALIZED SL-TECHNOLOGIE

2X DU: 240W UND 35NM MOTORLEISTUNG VERDOPPELN DEINE EIGENLEISTUNG

EFFIZIENZ: HOHE REICHWEITE MIT 320WH INTERNEM AKKU UND OPTIONALEN 160WH RANGE EXTENDER

SICHER: INTEGRIERTE LICHTANLAGE UND SCHEIBENBREMSEN SORGEN FÜR SICHERHEIT IN DER STADT

SPORTLICH: DIE FITNESS GEOMETRIE FÜR AGILES FAHREN AUF ASPHALT UND WALDWEGEN

KOMFORT: ANGENEHME SITZPOSITION UND EINFACHES AUF- UND ABSTEIGEN



VADO SL 5.0 EQ STEP-THROUGH



BRUSHED ALUMINUM / BLACK REFLECTIVE

BRUSHED ALUMINUM / BLACK REFLECTIVE

S	93921-3102
M	93921-3103
L	93921-3104
XL	93921-3105

VADO SL 5.0 EQ STEP-THROUGH

GEOMETRY

	S	M	L	XL
STACK (MM)	542	574	607	643
REACH (MM)	397	419	433	442
HEAD-TUBE LENGTH (MM)	130	161.5	194.5	230
HEAD-TUBE ANGLE (DEGREES)	70	70.5	71	71.5
BB HEIGHT (MM)	291	291	291	291
BB DROP (MM)	70	70	70	70
TRAIL (MM)	71	67	64	61
FORK LENGTH (FULL) (MM)	390	390	390	390
FORK RAKE / OFFSET (MM)	50	50	50	50
FRONT-CENTER (MM)	626	655	675	690
CHAIN-STAY LENGTH (MM)	445	445	445	445
WHEELBASE (MM)	1062	1091	1110	1126
TOP-TUBE LENGTH (HORIZONTAL) (MM)	558	587	610	630
BIKE STAND-OVER HEIGHT (MM)	616	631	655	688
SEAT-TUBE LENGTH (MM)	405	431.5	469.5	510
SEAT-TUBE ANGLE (DEGREES)	73.5	73.5	73.5	73.5
CRANK LENGTH (MM)	170	172.5	172.5	175
HANDLEBAR WIDTH (MM)	680	680	680	680
STEM LENGTH (MM)	60	75	75	90
SADDLE WIDTH (MM)	155	155	155	155
SEATPOST LENGTH (MM)	350	350	350	350

SPECS

CHF 5,199.00

Specifications subject to change without notice

FRAME	2020 Vado SL Step-Through
HEADLIGHT	Lezyne Ebike Power STVZO E115, 310Lumens, 12V
TAILLIGHT	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
KICKSTAND	Specialized kickstand, 40mm mount
RACK	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
FENDERS	Specialized DryTech, Aluminum
BELL	Simple bell
REAR DERAILLEUR	Shimano XT, Shadow Plus, SGS Cage, 12-speed
SHIFT LEVERS	Shimano SLX, Rapidfire Plus, 12-speed, w/o OGD
CASSETTE	Shimano SLX, Hyperglide+, 12-speed, 10-45t
CHAIN	Shimano SLX, 12-speed, w/Quick Link
CRANKSET	Crank Set, Praxis, PLW Fitness, PLW M30, Forged Arm, BCD 110mm, w/o Chainring, w/o CG
CHAINRINGS	SRAM Cring X-Sync 11S 44T w/ AG 110 AL5 BTBLK
PEDALS	Specialized Commuter w/ grip tape & reflectors
RIMS	DT Swiss R500 disc, 22mm internal width, 23mm internal depth
FRONT HUB	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
REAR HUB	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
SPOKES	DT Swiss Industry
FRONT TIRE	Nimbus II Sport Reflect, 700x38mm
REAR TIRE	Nimbus II Sport Reflect, 700x38mm
INNER TUBES	Presta, 40mm valve
SADDLE	Bridge Sport, hollow cr-mo rails, 155mm
SEATPOST	Specialized, alloy, 2-bolt, 12.5mm offset, 30.9mm
FORK	Future Shock 1.5, Boost™ 12x110mm thru-axle, flat mount disc, carbon fork
SEAT BINDER	Seat Collar, KCNC, SPL-SC02-308-02, Extruded, 7075-T73, 30.8mm, 10B21, Black Zinc Bolt, Bolt Clamp Type
MOTOR	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CHARGER	Custom charger, 48V System w/ SL system charger plug
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
STEM	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD-W mount
GRIPS	Body Geometry Women's Contour
HANDLEBARS	Stout Mini Rise, alloy, 9-degree backsweep, 15mm rise, 31.8mm
FRONT BRAKE	Tektro HD-R510, hydraulic disc, 160mm
REAR BRAKE	Tektro HD-R510, hydraulic disc, 160mm

VADO SL 4.0 EQ STEP-THROUGH



WHITE SAGE / BLACK REFLECTIVE

WHITE SAGE / BLACK REFLECTIVE

S	93921-5202
M	93921-5203
L	93921-5204
XL	93921-5205



RASPBERRY / BLACK REFLECTIVE

RASPBERRY / BLACK REFLECTIVE

S	93921-5302
M	93921-5303
L	93921-5304
XL	93921-5305

VADO SL 4.0 EQ STEP-THROUGH

GEOMETRY

	S	M	L	XL
STACK (MM)	542	574	607	643
REACH (MM)	397	419	433	442
HEAD-TUBE LENGTH (MM)	130	161.5	194.5	230
HEAD-TUBE ANGLE (DEGREES)	70	70.5	71	71.5
BB HEIGHT (MM)	291	291	291	291
BB DROP (MM)	70	70	70	70
TRAIL (MM)	71	67	64	61
FORK LENGTH (FULL) (MM)	390	390	390	390
FORK RAKE / OFFSET (MM)	50	50	50	50
FRONT-CENTER (MM)	626	655	675	690
CHAIN-STAY LENGTH (MM)	445	445	445	445
WHEELBASE (MM)	1062	1091	1110	1126
TOP-TUBE LENGTH (HORIZONTAL) (MM)	558	587	610	630
BIKE STAND-OVER HEIGHT (MM)	616	631	655	688
SEAT-TUBE LENGTH (MM)	405	431.5	469.5	510
SEAT-TUBE ANGLE (DEGREES)	73.5	73.5	73.5	73.5
CRANK LENGTH (MM)	170	172.5	172.5	175
HANDLEBAR WIDTH (MM)	680	680	680	680
STEM LENGTH (MM)	60	75	75	90
SADDLE WIDTH (MM)	155	155	155	155
SEATPOST LENGTH (MM)	350	350	350	350

SPECS

CHF 3,899.00

Specifications subject to change without notice

FRAME	2020 Vado SL Step-Through
HEADLIGHT	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
TAILLIGHT	Lezyne Ebike Rear Fender STVZO, 11Lumens, 12V
KICKSTAND	Specialized kickstand, 40mm mount
RACK	Turbo SL Rack, Closed Platform, direct fender mount, Racktime-compatible, 15kg
FENDERS	Specialized DryTech, Aluminum
BELL	Simple bell
REAR DERAILLEUR	Shimano Deore, Shadow Plus, GS cage, 10-speed
SHIFT LEVERS	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
CASSETTE	Shimano Deore, 10spd, 11-42t
CHAIN	KMC e10S, 10-speed w/ Missing Link™
CRANKSET	Praxis, Forged alloy M30, custom offset
CHAINRINGS	Praxis, 46T, 110BCD
PEDALS	Specialized Commuter w/ grip tape & reflectors
RIMS	700C disc, 22mm rim depth, 21mm internal width
FRONT HUB	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
REAR HUB	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
SPOKES	DT Swiss Industry
FRONT TIRE	Nimbus II Sport Reflect, 700x38mm
REAR TIRE	Nimbus II Sport Reflect, 700x38mm
INNER TUBES	Presta, 40mm valve
SADDLE	Bridge Sport, steel rails
SEATPOST	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
FORK	Rigid full aluminum disc, Boost™ 12x110mm, front- rack-compatible
SEAT BINDER	Seat Collar, KCNC, SPL-SC02-308-02, Extruded, 7075-T73, 30.8mm, 10B21, Black Zinc Bolt, Bolt Clamp Type
MOTOR	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+/Bluetooth®
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CHARGER	Custom charger, 48V System w/ SL system charger plug
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
STEM	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD-W mount
GRIPS	Body Geometry Women's Contour
HANDLEBARS	Stout Mini Rise, alloy, 9-degree backsweep, 15mm rise, 31.8mm
FRONT BRAKE	Tektro HD-R290, hydraulic disc, 160mm
REAR BRAKE	Tektro HD-R290, hydraulic disc, 160mm

VADO SL 4.0 STEP-THROUGH



LIMESTONE / BLACK REFLECTIVE

LIMESTONE / BLACK REFLECTIVE

S	93921-5002
M	93921-5003
L	93921-5004
XL	93921-5005



CAST UMBER / SILVER REFLECTIVE

CAST UMBER / SILVER REFLECTIVE

S	93921-5102
M	93921-5103
L	93921-5104
XL	93921-5105

VADO SL 4.0 STEP-THROUGH

GEOMETRY

	S	M	L	XL
STACK (MM)	542	574	607	643
REACH (MM)	397	419	433	442
HEAD-TUBE LENGTH (MM)	130	161.5	194.5	230
HEAD-TUBE ANGLE (DEGREES)	70	70.5	71	71.5
BB HEIGHT (MM)	291	291	291	291
BB DROP (MM)	70	70	70	70
TRAIL (MM)	71	67	64	61
FORK LENGTH (FULL) (MM)	390	390	390	390
FORK RAKE / OFFSET (MM)	50	50	50	50
FRONT-CENTER (MM)	626	655	675	690
CHAIN-STAY LENGTH (MM)	445	445	445	445
WHEELBASE (MM)	1062	1091	1110	1126
TOP-TUBE LENGTH (HORIZONTAL) (MM)	558	587	610	630
BIKE STAND-OVER HEIGHT (MM)	616	631	655	688
SEAT-TUBE LENGTH (MM)	405	431.5	469.5	510
SEAT-TUBE ANGLE (DEGREES)	73.5	73.5	73.5	73.5
CRANK LENGTH (MM)	170	172.5	172.5	175
HANDLEBAR WIDTH (MM)	680	680	680	680
STEM LENGTH (MM)	60	75	75	90
SADDLE WIDTH (MM)	155	155	155	155
SEATPOST LENGTH (MM)	350	350	350	350

SPECS

CHF 3,699.00

Specifications subject to change without notice

FRAME	2020 Vado SL Step-Through
HEADLIGHT	Lezyne Ebike Hecto STVZO E65, 210Lumens, 12V
TAILLIGHT	Specialized integrated saddle mount, LED Technology, 12V
BELL	Simple bell
REAR DERAILLEUR	Shimano Deore, Shadow Plus, GS cage, 10-speed
SHIFT LEVERS	Shimano Deore, RapidFire Plus, 10-speed w/ Optical Gear Display
CASSETTE	Shimano Deore, 10spd, 11-42t
CHAIN	KMC e10S, 10-speed w/ Missing Link™
CRANKSET	Praxis, Forged alloy M30, custom offset
CHAINRINGS	Praxis, 46T, 110BCD
PEDALS	Specialized Commuter w/ grip tape & reflectors
RIMS	700C disc, 22mm rim depth, 21mm internal width
FRONT HUB	Specialized alloy front hub disc, sealed cartridge bearings, 12x110mm, Center Lock™, 24h
REAR HUB	Specialized alloy rear hub disc, Center Lock™, sealed cartridge bearings, 12x148mm, 28h
SPOKES	DT Swiss Industry
FRONT TIRE	Specialized Pathfinder Sport, 700x38c
REAR TIRE	Specialized Pathfinder Sport, 700x38c
INNER TUBES	Presta, 40mm valve
SADDLE	Bridge Sport, Steel rails, 155mm
SEATPOST	Specialized, alloy, dual-bolt, 25mm offset, 27.2mm
FORK	Rigid full aluminum disc, Boost™ 12x110mm, front- rack-compatible
SEAT BINDER	Seat Collar, KCNC, SPL-SC02-308-02, Extruded, 7075-T73, 30.8mm, 10B21, Black Zinc Bolt, Bolt Clamp Type
MOTOR	Specialized SL 1.1, custom lightweight motor
UI/REMOTE	Specialized TCU, 10-LED State of charge, 3-LED Ride Mode display, ANT+ / Bluetooth®
BATTERY	Specialized SL1-320, fully integrated, 320Wh
CHARGER	Custom charger, 48V System w/ SL system charger plug
WIRING HARNESS	Custom Specialized wiring harness w/ chargeport
STEM	Specialized Stealth Stem, alloy, 14 deg, 31.8mm, integrated TCD-W mount
GRIPS	Body Geometry Women's Contour
HANDLEBARS	Stout Mini Rise, alloy, 9-degree backsweep, 15mm rise, 31.8mm
FRONT BRAKE	Tektro HD-R290, hydraulic disc, 160mm
REAR BRAKE	Tektro HD-R290, hydraulic disc, 160mm